

# 5mm Super Bright Green Blinking LED Lamps B500ITG4F

5mm Blinking with AlGaInP Dice

Encapsulated with Water Clear lens Package

Long Leads

Building in I.C. (2.4Hz)

### Absolute Maximum Ratings :

Parameter	Maximum Rating	Unit
Peak Forward Current	120	mA
Continuous Forward Current	30	mA
Operating Temperature Range	-20 to +75	
Storage Temperature Range	-40 to +100	
Lead Soldering Temperature	260 for 3 seconds 1.6mm (0.063 inch) from body	

### Electro-Optical Characteristics $T_a = 25$

Parameter Radiant	Test Condition	Symbol	Min.	Typ.	Max.	Unit
Forward Voltage	$I_f = 20\text{mA}$	$V_f$		2.0	2.4	V
Reverse Current	$V_r = 5\text{V}$	$I_r$			10	$\mu\text{A}$
Luminous Intensity	$I_f = 20\text{mA}$	$I_v$		1300		mcd
Spectral Bandwidth	$I_f = 20\text{mA}$	$\Delta\lambda$				nm
Wavelength	$I_f = 20\text{mA}$	$\lambda_p$		573		nm
		$\lambda_d$		570		nm
Half View Angle	$I_f = 20\text{mA}$	$2\theta_{1/2}$		30		deg

### Package

Item: 500

