

Verbatim LED Driver for 20W Recessed Downlight

- Power factor >0.9
- Flicker-free



Order Code	52941
General Data	
Primary Voltage Range (V)	200-240
Operating Frequency (Hz)	50-60
Input Current (A)	0.095
Output Current (A)	0.52
Secondary Voltage (V)	30-42
Input Wattage (W)	20 (with Verbatim LED "Trumpet" and Indirect Downlights)
Power Factor	>0.9
Ambient Temperature t_a (°C)	-10 to 50
Max Case Temperature t_c (°C)	65
Dimensions LxWxH (mm)	134x48x29
Weight (g)	120
Primary Terminal	No wire
Secondary Terminal	2-pole, pre-wired with dedicated connector
Standards	EN 60347-1
	EN 60347-2-13
	EN 55015
	EN 61000-3-2
	EN 61000-3-3
	EN 61547

Specifications are subject to operating with halogen lamps



Created October 2018

www.verbatimlighting.com

Verbatim LED Driver for 20W Recessed Downlight

Order Code	52941
Product Description	Verbatim LED Driver for 20W Recessed Downlight

Technical Packaging Details

Barcode	23942529415
Outer EAN 14	50023942529410
Inner EAN 128	(02)00023942529415(37)10(91)814
Pack Dimensions (HxWxL)	45mm x 50mm x 155mm
Pack Weight (g)	145
Carton Qty (Shipping Unit)	1
Cartons/pallet	135
Layers/Pallet	5
Units/Pallet	1350