



Poles	Dimensions mm	
	A	B
2	2.50	5.8
3	5.00	8.3
4	7.50	10.8
5	10.00	13.3
6	12.50	15.8
7	15.00	18.3
8	17.50	20.8
9	20.00	23.3
10	22.50	25.8
11	25.00	28.3
12	27.50	30.8
13	30.00	33.3
14	32.50	35.8
15	35.00	38.3
16	37.50	40.8

### Specifications

- ◆1、Poles: 2 to 16P
- ◆2、Current rating: 3.0A AC,DC
- ◆3、Voltage rating: 250V AC,DC
- ◆4、Temperature range: -25°C to +85°C
- ◆5、Contact resistance:  $\leq 20m\Omega$
- ◆6、Insulation resistance:  $\geq 1000M\Omega$
- ◆7、Withstand voltage: 1000V AC/minute
- ◆8、Applicable wire: AWG #28 to #22
- ◆9、Applicable PC board thickness: 1.6mm

1		Housing	PA66 (UL94V-0)	1	White
<b>SNA2505-HXX</b>					
		X.° ±3° X.X° ±0.5°		Design Units	SIZE
>0-3	>3-18	>18-50	>50-120	MM Only	METRIC A4
±0.12	±0.15	±0.3	±0.5		
					